

# NAOS IP

MODEL	TT-6519IP	TT-7519IP	TT-8619IP
<b>Display</b>			
Active Screen Size	65"	75"	86"
Backlight type	LED (WCG + Anti blue light Filter)		
Aspect ratio	16:9		
Resolution	3840 x 2160 (4K UHD)		
Display color	1,07 billion		
Brightness	≥400 cd/m <sup>2</sup>		
Contrast Ratio (Dynamic)	4000:1		
Viewing angle	178°		
Life Time	≥50.000 hours		
<b>Electrical</b>			
Power Consumption (Normal)	≤250 W	≤300 W	≤400 W
Power Consumption (Standby mode)	<0,5 W		
Working Voltage	AC 100-240 V; 50/60 Hz; Max 3,0 A		
<b>Touch</b>			
Surface treatment	Optical Bonding / Anti-glare tempered glass + Anti-fingerprint		
Touch type	Projective Capacitive Touch (P-cap)		
Writing pen	Fine passive pen		
Touch points	Windows 20 points		
<b>Speaker</b>			
Speaker Position	Downward		
Speaker Rated Impedance	8 Ω		
Speaker Max.Power Output	2 x 15 W		
<b>Transportation/Storage</b>			
Outline Dimension	1509 x 886 x 86 mm	1731 x 1010 x 86 mm	1977 x 1150 x 86 mm
Package size	1640 x 1036 x 221 mm	1859 x 1136 x 247 mm	2119 x 1281 x 275 mm
Net weight	36 Kg	49 Kg	60 Kg
Gross weight	46,5 Kg	62 Kg	76 Kg
VESA Mount	600 x 400 mm	800 x 400 mm	800 x 400 mm
<b>IO Ports</b>			
Rear input ports	HDMI 2.0 (4K@60 Hz) x 2; VGA (2K@60 Hz) x 1; USB-B 2.0 (Touch) x 1; VGA audio in (Jack 3,5 mm) x 1; USB-A 2.0 x 1; YPbPr x 1; RS232 (Serial) x 1		
Rear output ports	Line Out (Earphone Jack 3,5 mm) x 1; AV out x 1		
OPS port	Yes, 4K@60 Hz		
<b>Others</b>			
OPS PC	Available		
Firmware update	OTA		

## Univecs

Universal Computers Support SL

Calle Alerce 9

Local 1 -28041,

Madrid, España

TEL: +34 916939987

MOVIL: +34 645296845